

Product Information

AVENO Mineral Super 60

0002-000002



Description

AVENO Mineral Super 60 is a mineral mono-grade engine oil for petrol and diesel car engines with or without turbo-charging and commercial vehicle engines. AVENO Mineral Super 60 is characterized by its good high temperature properties, minimization of fuel consumption, friction and wear. With AVENO Mineral Super 60, a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Mineral Super 60 is designed for use in petrol and diesel car engines and commercial vehicle engines. AVENO Mineral Super 60 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SF/CF
- CCMC G4
- MIL-L-2104 D
- MIL-L-46152 B

Recommendation

- MB 227.0, MB 228.0

Properties

- A stable and excellent viscosity behavior
- Suitability for catalytic converters
- Prevention of black sludge formation
- Good detergent and dispersing properties
- A very good shear stability
- A high oxidation stability

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	306.5	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	23.8	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	98		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	897	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-12	°C	ASTM D 7346:2015
Total Base Number (TBN)	7.2	mgKOH/g	ASTM D 2896:2015