

# Product Information

## AVENO Mineral Super 70

0002-000076



### Description

AVENO Mineral Super 70 is a mineral mono-grade engine oil for petrol and diesel car engines with or without turbocharging and commercial vehicle engines. It is characterized by its good high temperature properties, minimization of fuel consumption, friction and wear. With AVENO Mineral Super 70, a reliable and heavy-duty engine oil has been developed.

### Instructions for use

AVENO Mineral Super 70 is designed for use in petrol and diesel car engines and commercial vehicle engines. The use is recommended for extremely high temperature. AVENO Mineral Super 70 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specification

- API CF/SF
- CCMC G4/D4/PD2
- MIL-L-2104 D
- MIL-L-46152 B

#### Recommendation

- MB 227.0, MB 228.0

### Properties

- Suitability for catalytic converters
- A very good shear stability
- A high oxidation stability
- A stable and excellent viscosity behavior
- Good detergent and dispersing properties
- Prevention of black sludge formation

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	481.0	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	31.2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	97		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	905	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-12	°C	ASTM D 7346:2015
Total Base Number (TBN)	7.1	mgKOH/g	ASTM D 2896:2015