

# Product Information

## AVENO Super Truck 50

0002-000088



### Description

AVENO Super Truck 50 is an HD engine oil, high-alloyed with synthetic additives suitable for diesel lorry engines, including with turbo charging. AVENO Super Truck 50 is characterized by its good cold starting properties, minimization of fuel consumption, friction and wear.

### Instructions for use

AVENO Super Truck 50 is an engine oil for year-round use, and is suitable for petrol and diesel car engines and commercial vehicle engines. AVENO Super Truck 50 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specification

- ACEA E2/B4
- API CF-4/SG
- MIL-L-2104 D
- MIL-L-46152 B

#### Recommendation

- Allison C-4
- Caterpillar TO-2
- Deutz DQC 1-02
- MB 228.0
- ZF TE-ML 04B/04E

### Properties

- Suitable for catalytic converters
- A very good shear stability
- A high oxidation stability
- A stable and excellent viscosity behavior
- Good detergent and dispersing properties
- Prevention of black sludge formation

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	200.2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	18.3	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	100		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	893	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-21	°C	ASTM D 7346:2015
Total Base Number (TBN)	9.5	mgKOH/g	ASTM D 2896:2015