

Product Information

AVENO DCT Super

0002-000166



Description

AVENO DCT Super is a fully synthetic gear fluid for dual-clutch gearboxes. AVENO DCT Super also guarantees a stable lubrication behavior under extreme stress in midsummer and low winter temperatures. AVENO DCT Super allows for practical non-slip operation and therefore a minimum loss of torque. AVENO DCT Super guarantees the low wear and long lifespan of the gearbox.

Instructions for use

AVENO DCT Super was designed especially for dual-clutch gearboxes from various car manufacturers such as Audi, BMW (Getrag), Citroen, Ford/Getrag, Mercedes-Benz, Mitsubishi, Nissan, Peugeot, Porsche, Seat, Skoda, Volkswagen, Volvo.

Recommendation

- Audi/VW/Bentley 6 speed, 7 speed, DSG7
- BMW 6-speed DCT, DCTF-1+, DCTF-2, 83 22 2 446 673
- BMW 83 22 0 440 214
- BMW 83 22 2 147 477
- BMW 83 22 2 148 578
- BMW 83 22 2 148 579
- BMW 83 22 2 433 157, Drivelogic 7-speed, MTF LT-5
- BMW DCTF-1
- Borg Warner Wet DCT
- Ford WSS-M2C936-A
- MB 236.21
- Mitsubishi MZ320065 Diaqueen SSTF-I
- Peugeot/Citroën 9734.S2
- Porsche 999.917.080.00
- VOLVO 1161838, VOLVO 1161839
- VW TL 52 182 A2, VW TL 52 529
- Bugatti Veyron (Wet DCT)
- BYD 6DT35, Q/BYD-A1909, 0058-2013
- Chrysler P/N 68044345EA, 68044345GA, 6-Speed
- Ferrari 7-speed, TE DCT-3
- Ford P/N 1490761, P/N 1490763, Powershift 6-speed
- MB 236.22, MB 236.24, MB 236.25, MB 239.21
- Mitsubishi TC-SST 6-speed
- Nissan 999MP-GTRT00P
- PDK DCT Transmission Oil for ZF
- Peugeot/Citroen DCS 6-speed
- Porsche 999.917.080.01, P/N 000 043 201 44, PDK DCT
- Renault EDC 6 speed, EDC 7 speed, Talisman R7D
- Volvo Powershift 6-speed
- VW 052 549
- ZF 8DT, TE-ML 11

Properties

- Low wear
- Excellent viscosity-temperature characteristics
- Neutral towards sealing agents
- Very low pour point
- Very good lubrication properties, even at low temperatures in winter
- Excellent protection against wear, corrosion and foaming
- Stable lubrication film, even under extreme conditions in midsummer

Technical specifications

Properties	Data	Unit	Testing under
Kinematische Viskosität bei 40°C	35.4	mm ² /s	DIN 51659-2:2017-02
Kinematische Viskosität bei 100°C	7.3	mm ² /s	DIN 51659-2:2017-02
Viskositätsindex	177		DIN ISO 2909:2004-08
Aussehen	YELLOWBROWN		VISUELL
Dichte bei 15°C	845	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-51	°C	ASTM D 7346:2015