

# Product Information

## AVENO LHM + Fluid GREEN

0002-000260



### Description

AVENO LHM + Fluid is a special hydraulic oil based on synthetic and mineral oils with high quality additives. Due to its special formulation, the properties of AVENO LHM + Fluid become decisively certain. We guarantee excellent cold stability.

### Instructions for use

AVENO LHM + Fluid is designed for the application range from -40 °C to +130 °C and thus becomes recommended for the latest developments in the vehicle market. AVENO LHM + Fluid has optimal performance as a central hydraulic oil in power steering, rear axle steering, leveling, hydropneumatic suspension, shock absorbers, for active damping and engine support, for hydrostatic drive of fan, alternator and air conditioning, for stability and traction systems (ABS / ASR / ASC), central locking, electrohydraulic convertible top control, hydraulic brake booster and hydropneumatic suspension for VW, Audi, Seat, Skoda. Especially suitable for use in cold countries.

### Quality classification

#### Specification

- ISO 7308

#### Recommendation

- Land Rover Cold Climate PAS Fluid 14315 LRN2261
- Peugeot/Citroën 9979 A1
- MB 343.0
- Saab 93160548
- Opel 1940 766
- Volvo 30741424
- PSA B71 2710
- VW G 004 000

### Properties

- Reliable protection against corrosion
- Improved viscosity and friction behaviour
- An excellent thermal stability
- Neutral towards sealing agents
- Extremely low pour point
- A very good wear protection
- A good foaming behaviour

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	25.2	mm <sup>2</sup> /s	DIN ISO 51562-2:1988-12
Kinematic Viscosity at 100°C	7.1	mm <sup>2</sup> /s	DIN ISO 51562-2:1988-12
Viscosity index	272		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Density at 15°C	840	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-69	°C	ASTM D 7346:2015