Product Information AVENO FS PAO CLP 220

0002-000289



Description

AVENO FS PAO CLP 220 is produced on a basis of high-quality synthetic oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, high-pressure capacity under impact loads. Due to the low pour point of AVENO FS PAO CLP 220, the cold flow behavior of this product is excellent.

Instructions for use

AVENO FS PAO CLP 220 can be used in every industrial gear that requires the application of a fully synthetic CLP gear oil according to DIN 51517 Part 3. With AVENO FS PAO CLP 220 heavily loaded gears running under temperatures up to 150°C can be lubricated reliably without tarnishing the components made of copper/brass.

Quality classification				
Specification				
• AGMA 9005-D94		• DIN 51517-3	• DIN 51517-3	
Recommendation				
Cincinnati Milacron		• US Steel 224		
Clean Panel Coker		• US Steel S-200	• US Steel S-200	
Properties				
An excellent cold flow behavior		• A stable, high-pressu	A stable, high-pressure capacity under impact loads	
An excellent wear protection		 A low pour point 	• A low pour point	
• Inhibits rust and corrosion		 Prevents foam forma 	Prevents foam formation	
Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	218.8	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	30.1	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	181		DIN ISO 2909:2004-08	
Appearance	LIGHT YELLOW		VISUELL	
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-54	°C	ASTM D 7346:2015	