Product Information

AVENO CLP 32

0002-000292



Description

AVENO CLP 32 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, highpressure capacity under impact loads. Due to the low pour point of AVENO CLP 32, the cold behavior of this product is excellent.

Instructions for use

AVENO CLP 32 has very good properties as a lubricant. AVENO CLP 32 can therefore be used in largely all industrial areas under stress and impact loads.

Quality classification			
Specification			
• AGMA 9005-D94		• DIN 51517-3	
Recommendation			
• Cincinnati Milacron • Clean Panel Coker		• US Steel 224 • US Steel S-200	
Properties			
 A low pour point An excellent wear protection Prevents foam formation Zinc free 		 A stable, high-pressure capacity under impact loads An excellent cold behavior Inhibits rust and corrosion 	
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	31.4	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	5.7	mm²/s	DIN 51659-2:2017-02
Viscosity Index	122		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	852	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.