## **Product Information**

## **AVENO CLP 460**

0002-000299



ASTM D 7346:2015

## Description

Pour Point

-12

AVENO CLP 460 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, highpressure capacity under impact loads. Due to the low pour point of AVENO CLP 460, the cold behavior of this product is excellent.

## Instructions for use

AVENO CLP 460 has very good properties as a lubricant. AVENO CLP 460 can therefore be used in largely all industrial areas under stress and impact loads.

| Quality classification   |             |  |                          |
|--|-------------|--|--------------------------|
| Specification  |             |  |                          |
| • AGMA 9005-D94  |             | • DIN 51517-3  |                          |
| Recommendation   |             |  |                          |
| <ul><li>Cincinnati Milacron</li><li>Clean Panel Coker</li></ul>  |             | • US Steel 224<br>• US Steel S-200   |                          |
| Properties   |             |  |                          |
| <ul> <li>A low pour point</li> <li>An excellent wear protection</li> <li>Prevents foam formation</li> <li>Zinc free</li> </ul> |             | <ul> <li>A stable, high-pressure capacity under impact loads</li> <li>An excellent cold behavior</li> <li>Inhibits rust and corrosion</li> </ul> |                          |
| Technical specifications   |             |  |                          |
| Properties   | Data        | Unit   | Testing under            |
| Kinematic Viscosity at 40°C  | 469.3       | mm²/s  | DIN 51659-2:2017-02      |
| Kinematic Viscosity at 100°C   | 30.9        | mm²/s  | DIN 51659-2:2017-02      |
| Viscosity Index  | 103         |  | DIN ISO 2909:2004-08     |
| Appearance   | YELLOWBROWN |  | VISUELL                  |
| Density at 15°C  | 899         | kg/m³  | DIN EN ISO 12185:1997-11 |

°C

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.