Product Information

AVENO TDL Ultimate 75W-90

0002-000819



Description

AVENO TDL Ultimate 75W-90 is a fully synthetic axle transmission oil. It was developed to meet the latest requirements of Mercedes Benz and other commercial vehicle axle manufacturers.

Instructions for use

AVENO TDL Ultimate 75W-90 is used for commercial vehicle axles. It is particularly recommended for axles that are used under tough operating conditions and heavy loads, as well as for non-synchronized manual transmissions. AVENO TDL Ultimate 75W-90 can be used wherever the manufacturer recommends a lubricant in accordance with MB 235.8.

Quality classification	
Specification	
• API GL-4/5	• MIL-PRF-2105 E
• API MT-1	• SAE J2360
Approval	
• MAN 341 GA1	• DTFR 12B140 (235.8)
• MAN 341 Z2	• ZF TE-ML 02B, 05A, 12L, 12N (ZF010792)
• MAN 342 S1	• ZF TE-ML 16F, 17B, 19C, 21A (ZF010792)
• Scania STO 1:1 G	
Recommendation	
Arvin Meritor 076-N	• MAN 342 Typ M3
• DAF	• Renault
• DFS 93K219.01	• Scania STO 2:0 A FS
• Iveco	• VOLVO 97312
• Mack GO-J	• ZF TE-ML 07A/12B/13

Properties

Thermally stable	 Extended oil change intervals
High viscosity index	 Use at low operating temperatures

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	106.7	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	15.8	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	158		DIN ISO 2909:2004-08	
Appearance	YELLOW		VISUELL	
Density at 15°C	871	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-57	°C	ASTM D 7346:2015	